

Tableau des hauteurs de montage maximales

	SPEC.	CULOT	VOLTAGE (V)	PUISSANCE (W)	NO DE CATALOGUE DE SAP	OUTPUT (LM)	HAUTEURS DE MONTAGE MAXIMALES (PI)
INCANDESCENCE	TUNGSTEN	WEDGE	6	7.2	50405	86	20
				9	50400	119	21
			12	9	50402	133	19
				12	BLUC-576000048	86	23
			24	18	50404	199	25
				9	LIT024V009WW	113	20
	QUARTZ	À DEUX BROCHES, (H3)	6	12	13631	178	24
				12	13626	252	29
			12	20	13625	299	66
	MR16	À DEUX BROCHES	12	55 (H3)	BLUC-576000109	381	31
20				BLUC-576000111	302	18	
35				BLUC-576000128	377	54	
DEL	MR16	À DEUX BROCHES (DEL)	6	50	50893	583	66
				5	BLUC-576000706	466	40
			12	7	BLUC-576000702	533	42
				2	BLUC-576000563	184	31
				5	BLUC-576000706	466	40
				5	BLUC-576000701	582	47
			24	7	BLUC-576000703	647	48
				5	BLUC-576000706	466	40
				5	BLUC-576000701	570	47
				7	BLUC-576000703	647	48
PAR36 (PHARE SCÉLLÉ)	GX5.3 SCREW TERMINAL	12	6	BLUC-576000576	434	71	
TESTA (SQUARE)	N/A	12	5	IHO-12-24V5W-BK	639	65	
			9	IHO-12-24V9W-BK	1100	85	
			14	IHO-12-24V14W-BK	1454	98	
		24	5	IHO-12-24V5W-BK	656	65	
			9	IHO-12-24V9W-BK	1110	83	
			14	IHO-12-24V14W-BK	1481	99	
		12~24	30	BLUC-576000579	2578	140	

Les IES/Photométries sont disponibles pour téléchargement sur les pages produits.